

## Technical data sheet

PVC control cables · C-track compatible · unshielded

### LÜTZE SUPERFLEX® 2000 PVC For medium to high requirements



#### Identification

Type	SU 2000 PVC 5G2,5
Part-No.	100187

#### Product version

Datasheet version	00
-------------------	----

#### Use/Application/Properties

Application	<ul style="list-style-type: none"><li>• Machine and device construction, transport and conveyor technology, heating and climate technology</li><li>• In dry and damp rooms</li><li>• As control and control cable in continuously moving applications</li><li>• For installation in energy chains with constant linear movement</li></ul>
Properties	<ul style="list-style-type: none"><li>• Construction and material suitable for continuous movement application</li><li>• PVC Flame-retardant, self-extinguishing</li><li>• Largely resistant to oils, greases, acids and bases</li><li>• Silicone free</li><li>• RoHS compliant</li></ul>

#### Construction

Description	SUPERFLEX® 2000 PVC
Number of conductors/cross-section	5G2.5
Number of conductors	5
Cross-section, metric	2.5 mm <sup>2</sup>
Jacket material	Special PVC
Jacket color	grey RAL 7001
Outer Ø	10.2 mm
Weight	18 kg/100 m
Cu-Index	12 kg/100 m

#### United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington · GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 · Fax +44 (0)1827 31333-2  
www.lutze.com · sales.gb@lutze.co.uk

#### Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) · Bruckwiesenstraße 17-19 · D-71384 Weinstadt  
Tel. +49 (0)7151 6053-0 · Fax +49 (0)7151 6053-277(-288)  
www.luetze.de · info@luetze.de

26.02.2021 · Subject to technical modification  
Part-No. 100187 · Datasheet version: 00

## Technical data sheet

PVC control cables · C-track compatible · unshielded

---

### Construction Element 1

---

Element construction	5G2.5
Conductor	CU-wire bare
Conductor category	DIN EN 60228, class 6 Superfinely stranded DIN VDE 0295 IEC 60228, Class 6
Conductor marking	black · with white number print · green/yellow
Conductor marking standard	DIN EN 50334
Conductor insulation	TPE

---

### Technical data

---

Rated voltage $U_0/U$	300/500 V
Test voltage type	3000 V
Temperature range moving	-15 °C ... +80 °C
Temperature range fixed	-30 °C ... +80 °C
Minimum bending radius moving	7.5×D
Minimum bending radius fixed	4×D
Bending cycles	≥5 Mio

---

### Overall construction

---

Overall stranding	conductors layered construction conductors twisted without mechanical stress layer pitch optimised
Overall wrapping	Fleece taping
Jacket characteristics	Silicone-free Flame-retardant

---

### Technical Data Element 1

---

Element construction	5G2.5
Insulation resistance at 20 °C	≥1000 MΩ×km
Operating capacitance wire-wire	approx. 80 pF/m

---

### Certifications/Standards

---

Conformity	REACH RoHS CE
Burning behavior according to	DIN EN 60332-2-2 VDE 0482-332-2-2

---

### General

---

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	----------------------------------------------------------------------------------

---